

短节距精密滚子链链轮

Short pitch precision roller chain wheels

5/8"×3/8" 10A-1-2-3 GB1244-1997 DIN8187 ISO/R606		链轮齿部参数MM		
		节距	P	15.875
		滚子直径	$d-\phi$	10.16
		元弧半径	r3	16
		倒角宽度	C	1.6
		齿宽	B1	8.7
		齿宽	b1	8.4
齿宽	B2	26.5		
齿宽	B3	44.6		

A型单排平片链轮
A type simplex plate wheels

A型双排平片链轮
A type duplex plate wheels

A型叁排平片链轮
A type triplex plate wheels

齿数 Z	外径 de	节径 dp	单排链轮			双排链轮			叁排链轮		
			Simplex			Duplex			Triplex		
			dm	D1	A	dm	D2	A	dm	D3	A
8	48.4	41.48	25	10	25						
9	53.3	46.32	30	10	25						
10	58.3	51.37	35	10	25						
11	63.2	56.34	37	12	30	35	12	40			
12	68.2	61.34	42	12	30	40	16	40	44	16	55
13	73.2	66.32	47	12	30	44	16	40	50	16	55
14	78.2	71.34	52	12	30	49	16	40	54	16	55
15	83.2	76.36	57	12	30	54	16	40	59	16	60
16	88.3	81.37	60	12	30	59	16	45	64	16	60
17	93.3	86.39	60	12	30	64	16	45	69	16	60
18	98.3	91.42	70	14	30	69	16	45	74	16	60
19	103.3	96.45	75	14	30	74	16	45	79	16	60
20	118.3	101.49	75	14	30	79	16	45	84	16	60
21	113.4	106.52	80	16	30	84	16	45	85	16	60
22	118.4	111.55	80	16	30	85	20	45	105	20	60
23	123.5	116.57	80	16	30	90	20	45	120	20	60
24	128.5	121.62	80	16	30	95	20	45			
25	133.6	126.66	80	16	30	100	20	45			
26	138.6	131.7	90	20	35	105	20	45			
27	143.6	136.75	90	20	35	110	20	45			
28	148.7	141.78	90	20	35	110	20	45			
29	153.7	146.83	95	20	35	115	20	45			
30	158.8	151.87	95	20	35	120	20	45			
31	163.8	156.92	95	20	35	120	20	45			
32	168.9	161.95	95	20	35	120	20	45			
33	173.9	167	95	20	35	120	20	45			
34	178.9	172.05	100	20	35	120	20	45			
35	184	177	100	20	35	120	20	45			
36	189	182.05	100	20	35	120	20	45			
37	194.1	187.2	100	20	35	120	20	45			
38	199.1	192.24	100	20	35	120	20	45			
39	204.2	197.29	100	20	35	120	20	45			
40	209.2	202.34	100	20	35	120	20	45			
42	220.8	212.44	100	20	35	120	20	45			
45	236	227.58	110	20	35	120	20	45			
48	251.1	242.73	110	20	35	120	20	45			
50	261.2	252.92	110	25	35	120	20	45			
54	281.4	273.03	110	25	35	120	20	45			
57	296.6	288.18	110	25	35	120	20	45			
60	311.7	303.32	110	25	35	120	20	45			

